


Feed-Through Panel Type Terminal Blocks



Compact design for panel mounting by flanged.

Spring cage design wiring structure for anti-vibration.

Standard 2 & 4 wirings per connection points are available.

Available accessories include insertion bridges and marking labels.

Design is compliant with IEC 60947-4-1 and UL 1059.


PM..W



PM2.5W		
Safety certification	UL IEC	
Specification	UL	IEC
Rated Voltage	600V	800V
Rated Current	25A	24A
Solid wire(AWG/mm ²)	28-12 / 0.5~2.5	
Stranded wire(AWG/mm ²)	14-12 / 0.5~2.5	
Rated impulse voltage	8KV	
Torque(N-m)		
Screws		
Stripping length	8~10mm	
Insulation materials	PA	
TxHxW(mm)	5.1x32x22	
Package	100	

Color	Part number	Package
●	PM2.5W-02P-12P-RD	50
●	PM2.5W-02P-12P-BL	50
●	PM2.5W-02P-12P-YG	50



Accessories	Part number	Package
(左)	PM2.5WCA	50
(右)	PM2.5WCB	50
2 way	CSC-2.502P	2~4P/50
⋮		
10way	CSC-2.510P	5~10P/10
	TM20	10
	0.4X2.5mm	/



PMM2.5W		
Safety certification	UL IEC	
Specification	UL	IEC
Rated Voltage	600V	800V
Rated Current	25A	24A
Solid wire(AWG/mm ²)	28-12 / 0.5~2.5	
Stranded wire(AWG/mm ²)	14~12 / 0.5~2.5	
Rated impulse voltage	8KV	
Torque(N-m)		
Screws		
Stripping length	8~10mm	
Insulation materials	PA	
TxHxW(mm)	10x32x22	
Package	100	

Color	Part number	Package
●	PMM2.5W-02P-11P-RD	50
	PMM2.5W-12P-RD	20
●	PMM2.5W-02P-11P-BL	50
	PMM2.5W-12P-BL	20
●	PMM2.5W-02P-11P-YG	50
	PMM2.5W-12P-YG	20





Accessories	Part number	Package
	PM2.5WCA	50
	PM2.5WCB	50
	TM20	10
	0.4X2.5mm	/



Safety certification		
Specification	UL	IEC

Color	Part number	Package

Accessories	Part number	Package



Assembled blocks	End cover	Single block	End cover with spring clamp
PM2.5W-XXP	PM2.5WCA	PM2.5W	PM2.5WCB
PMM2.5W-XXP	PMM2.5WCA	PMM2.5W	PMM2.5WCB