



NO POSN	DIM A
2	16.6 ± 0.3
3	26.6 ± 0.5
4	36.6 ± 0.5
5	46.6 ± 0.7
6	56.6 ± 0.7
7	66.6 ± 0.7
8	76.6 ± 1.0
9	86.6 ± 1.0
10	96.6 ± 1.0
11	106.6 ± 1.5
12	117.2 ± 1.5

ALL DIMENSION IN MM UNLESS OTHERWISE STATED : 0.= ±0.2mm 00.= ±0.4mm

Housing Material : Polyamide 66 (PA66), Nature flame-retardant to UL 94V-2

Voltage : 300V(UL), 450V(VDE)

Current : 30A(UL), 24A(VDE)

Working Temperature : T110(IEC), 105 ° C(UL)

Insert : Brass, nickel-plated

Screws : M3.0x6, Steel zinc-plated

Wire Range : 1.0 ~ 2.5mm², #22 ~ #10 Sol. #14 ~ #10 Str.

International Approvals

UL, CSA, CE, VDE, FIMKO, SEMKO, NEMKO, DEMKO, KEMA, OVE, CEBEC, SEV, CQC, IMQ

金筆企業股份有限公司
HEAVY POWER CO., LTD.

TITLE :
TERMINAL BLOCK
Model NO.PA10
Part NO.PA10H

Drawn By

yao

2014.11.13

Rev.

A1